

CRAWLER EXCAVATOR ZE550G

| | | Items | ZE550G |
|---|----------------------------|----------------------------------|--------------------------------|
| | Basic Technical Data | Operating Weight | 53500 kg |
| | | Standard bucket capacity (Range) | HD 3.2 m³ (2.85 m³ - 4.0 m³) |
| | | Slewing Speed | 8.4 r/min |
| | | Traveling Speed(high/low) | 5.2/3.2 km/h |
| | | Max. Drawbar Pull | 443 kN |
| | | Digging Force of Bucket | 329 kN |
| | | Digging Force of Stick | 271 kN |
| | Engine | Engine Manufacturer | Cummins |
| | | Engine Model | X12S3A375 |
| | | Rated Power | 277 kW / 2100 rpm |
| | | Displacement | 11.8L |
| | | Emission Standard | EU Stage IIIA |
| | Dimensions | Length | 11790 mm |
| | | Width | 3610 mm |
| | | Height | 3990 mm |
| | | Boom Length | 6500 mm |
| | | Stick Length | 3000 mm |
| | | Tail Slewing Radius | 3887 mm |
| | | Track Gauge | 2750 mm |
| | | Length of Track on Ground | 4400 mm |
| | Operating Range | Max. Digging Radius | 10982 mm |
| | | Max. Digging at Ground Level | 10740 mm |
| | | Max. Digging Depth | 6945 mm |
| | | Max. Digging Height | 9686 mm |
| 1 | | Max. Dumping Height | 6644 mm |







