ZOOMLION

ELECTRIC ARTICULATING BOOM LIFT

ZA10RJE

Comply with CE/ANSI/CSA Standard



HIGHLIGHTS

- Center layout, great structural rigidity, and small boom deflection
- Advanced dual control system (valve control + pump control) offers a energy-saving, smooth and efficient control
- ±90° Jib rotation offers great up and over height
- Compact dimension of 1.19m (3ft 11in) stowed width, ideal for narrow working conditions
- Tubular batteries feature long working time and lifespan, and easy for maintenance

FEATURES

Standard Features

Proportional control	Load sensing system
All motion alarm	4.3' LED display
Flashing beacon	Horn
Self-closing entry gate	Timer
Emergency descent system	Jib rotation
Emergency stop button	Vertical lifting function
Auto-leveling system	Thumb joystick for steering
On-board diagnostic system	35A battery smart charger
Over tilt protection system	Battery level display
Solid seamless tire	Low electric quantity protection

Accessories & Options

- Platform light
- AC power to platform
- Airline to platform
- Electric auxiliary pump
- Platform console cover (Rated capacity reduced by 10kg)
- Anti-crushing device (Rated capacity reduced by 10kg)

ACCESS WITH ZOOMLION GREEN

Phone: 0086(731)-88353692
E-mail: awp@zoomlion.com

Add: 701 Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China
Web: www.zoomlion-access.com

ZOOMLION

Model	ZA10RJE	
	Imperial	Metric
Dimension		
Work Height	37ft 11in	11.55m
Platform Height	31ft 4in	9.55m
Horizontal Outreach	22ft 5in	6.85m
Up and Over Height	15ft 1in	4.6m
A - Stowed Length	18ft 1in	5.5m
B - Stowed Width	3ft 11in	1.19m
C - Stowed Height	6ft 6in	1.98m
D - Platform Length	3ft 10in	1.17m
E - Platform Width	2ft 6in	0.76m
Jib length	4ft 1in	1.24m
F - Wheelbase	5ft 5in	1.65m
G - Ground Clearance	4in	0.1m
I - Transport Length (Jib tucked under)	13ft	3.95m
J - Transport Height (Jib tucked under)	8ft	2.45m
Performance		
Platform Capacity	510lb	230kg
Drive Speed	3.11mph	5km/h
Gradeability	35% (19°)	35% (19°)
Turning Radius (Inside)	5ft 7in	1.7m
Turning Radius (Outside)	10ft 8in	3.25m
Turntable Swing	355° non-continuous	
Jib Swing	±90°	
Platform Rotation	±90°	
H-Tail Swing	0m	
Max. Wind Speed	28mph	12.5m/s
Power		
Battery	24×2V/330Ah	
Charger	48V/35A	
Drive Motor	AC 32V	
Lift Motor	DC 48V	
Auxiliary Power	Electric pump	
Hydraulic Tank Capacity	3.96(us gal)	15L
Tire		
Type	Non-marking tire	
Weight		
Gross	14440lb	6550kg







Range of Motion ZA10RJE



Range of Jib Swing Motion ZA10RJE

ZOOMLION ACCESS reserves the right to make specification and/or equipment changes without prior notification.
Product specifications are updated to January, 2025.